

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A method for communicating between a client device and a peripheral device over a network that includes the peripheral device, the client device, and a server device adapted to control the peripheral device, the peripheral device having a network address which is not known to the client device, wherein the method is performed by the client device, the method comprising:

determining the network address of the peripheral device, wherein determining includes:

retrieving a first data file from the server device, wherein the first data file is a web page;

identifying one or more portions of the retrieved first data file as potential network addresses;

reading a first data file of the server device, said first data file including at least one of (a) the network address of the peripheral device, and (b) a network address of a second data file associated with and including the network address of the peripheral device, and

comparing the one or more potential network addresses of the retrieved first data file portions of at least one of said first and second data files with a predetermined data formatting pattern indicative of a network address;

identifying one or more potential network addresses of the retrieved first data file as network addresses; and

determining if a network address is the network address of the peripheral device;

addressing the peripheral device using the determined network address of the peripheral device; and

communicating directly with the peripheral device, thereby bypassing the server device.

2. (Currently Amended) The method of claim 1, wherein said first data file includes (a) the network address of the peripheral device, and wherein said step of determining the network address of the peripheral device comprises comparing portions of said first data file with said pattern.

3. (Currently Amended) The method of claim 2, wherein said step of determining the network address of the peripheral device further comprises recognizing a match between a potential network address portion of said first data file and said pattern, identifying the potential network address as a network address, and identifying said network address portion as being the network address of the peripheral device.

4. (Currently Amended) The method of claim 1, wherein said first data file includes (b) the network address of a second data file associated with and including the network address of the peripheral device, and wherein said step of determining the network address of the peripheral device comprises:

retrieving the second data file from the server device, wherein the second data file is a web page;

identifying one or more portions of the retrieved second data file as potential network addresses; and

comparing portions of said second data file with said pattern.

5. (Currently Amended) The method of claim 4, wherein said step of determining the network address of the peripheral device further comprises recognizing a match between a potential network address portion of said second data file and said pattern, identifying the potential network address as a network address, and identifying said network address portion as being the network address of the peripheral device.

6. (Currently Amended) The method of claim 5, wherein said step of determining if a network address is the network address of the peripheral device further comprises testing said network address ~~portion~~ to determine whether said network address is the network address of the peripheral device.

7. (Original) The method of claim 6, wherein said testing comprises sending a command to said network address.

8. (Currently Amended) The method of claim 6, wherein said step of determining if a network address is the network address of the peripheral device further comprises identifying said network address ~~portion~~ as being the network address of the peripheral device as a result of said testing.

9. (Currently Amended) A memory readable by a machine embodying a program of instructions executable by the machine to facilitate communication between a client device and a peripheral device over a network that includes the peripheral device, the client device, and a server device adapted to control the peripheral device, the peripheral device having a network address which is not known to the client device, the instructions being configured to:

determine the network address of the peripheral device, wherein determining includes:

retrieving a first data file from the server device, wherein the first data file is a web page;

identifying one or more portions of the retrieved first data file as potential network addresses;

~~reading a first data file of the server device, said first data file including at least one of (a) the network address of the peripheral device, and (b) a network~~

~~address of a second data file associated with and including the network  
address of the peripheral device, and~~  
comparing the one or more potential network addresses of the retrieved first data  
~~file portions of at least one of said first and second data files with a~~  
predetermined data formatting pattern indicative of a network address;  
~~identifying one or more potential network addresses of the retrieved first data file~~  
~~as network addresses; and~~  
~~determining if a network address is the network address of the peripheral device;~~  
address the peripheral device using the determined network address of the peripheral  
device; and  
communicate directly with the peripheral device, thereby bypassing the server device.

10. (Currently Amended) The memory of claim 9, wherein said first data file includes (a) the network address of the peripheral device, and wherein said step of determining the network address of the peripheral device comprises comparing portions of said first data file with said pattern.

11. (Currently Amended) The memory of claim 10, wherein said step of determining the network address of the peripheral device further comprises recognizing a match between a potential network address portion of said first data file and said pattern, identifying the potential network address as a network address, and identifying said network address ~~portion~~ as being the network address of the peripheral device.

12. (Currently Amended) The memory of claim 9, wherein said first data file includes (b) the network address of a second data file associated with and including the network address of the peripheral device, and wherein said step of determining the network address of the peripheral device comprises:

retrieving the second data file from the server device, wherein the second data file is a web page;  
identifying one or more portions of the retrieved second data file as potential network addresses; and  
comparing portions of said second data file with said pattern.

13. (Currently Amended) The memory of claim 12, wherein said step of determining the network address of the peripheral device further comprises recognizing a match between a potential network address portion of said second data file and said pattern, identifying the potential network address as a network address, and identifying said network address ~~portion~~ as being the network address of the peripheral device.

14. (Currently Amended) The memory of claim 13, wherein said step of determining if a network address is the network address of the peripheral device further comprises testing said network address ~~portion~~ to determine whether said network address is the network address of the peripheral device.

15. (Previously Presented) The memory of claim 14, wherein said testing comprises sending a command to said network address.

16. (Currently Amended) The memory of claim 14, wherein said step of determining if a network address is the network address of the peripheral device further comprises identifying said network address ~~portion~~ as being the network address of the peripheral device as a result of said testing.

17. (Currently Amended) A computing device for communicating with a peripheral device over a network that includes the peripheral device, the computing device, and a server device

adapted to control the peripheral device, the peripheral device having a network address which is not known to the computing device, comprising:

means for determining the network address of the peripheral device, wherein determining includes:

retrieving a first data file from the server device, wherein the first data file is a web page;

identifying one or more portions of the retrieved first data file as potential network addresses;

reading a first data file of the server device, said first data file including at least one of (a) the network address of the peripheral device, and (b) a network address of a second data file associated with and including the network address of the peripheral device, and

comparing the one or more potential network addresses of the retrieved first data file portions of at least one of said first and second data files with a predetermined data formatting pattern indicative of a network address;

identifying one or more potential network addresses of the retrieved first data file as network addresses; and

determining if a network address is the network address of the peripheral device;

means for addressing the peripheral device using the determined network address of the peripheral device; and

means for communicating directly with the peripheral device, thereby bypassing the server device.

18. (Currently Amended) The computing device of claim 17, wherein said first data file includes (a) the network address of the peripheral device, and wherein said means for determining the network address of the peripheral device comprises comparing portions of said first data file with said pattern.

19. (Currently Amended) The computing device of claim 18, wherein said means for determining the network address of the peripheral device further comprises means for recognizing a match between a potential network address ~~portion~~ of said first data file and said pattern, means for identifying the potential network address as a network address, and means for identifying said network address ~~portion~~ as being the network address of the peripheral device.

20. (Currently Amended) The computing device of claim 17, wherein said first data file includes (b) the network address of a second data file associated with and including the network address of the peripheral device, and wherein said means for determining the network address of the peripheral device comprises:

means for retrieving the second data file from the server device, wherein the second data file is a web page;

means for identifying one or more portions of the retrieved second data file as potential network addresses; and

means for comparing portions of said second data file with said pattern.

21. (Currently Amended) The computing device of claim 20, wherein said means for determining the network address of the peripheral device further comprises means for recognizing a match between a potential network address ~~portion~~ of said second data file and said pattern, means for identifying the potential network address as a network address, and means for identifying said network address ~~portion~~ as being the network address of the peripheral device.

22. (Currently Amended) The computing device of claim 21, wherein said means for determining if a network address is the network address of the peripheral device further comprises means for testing said network address ~~portion~~ to determine whether said network address is the network address of the peripheral device.

23. (Previously Presented) The computing device of claim 22, wherein said means for testing comprises means for sending a command to said network address.

24. (Currently Amended) The computing device of claim 22, wherein said means for determining if a network address is the network address of the peripheral device further comprises means for identifying said network address ~~portion~~ as being the network address of the peripheral device as a result of the determination performed by said means for testing.